

Instruction - glass products

1. Products for indoors application only.
2. During warehousing, the products should be protected against contact with water and sub-zero temperatures.
3. When accepting the products, they should be inspected to identify any possible damage and to confirm quantity.
4. Verify the quality of surface, dimensions and shades of the received products before laying them.
5. Any changes in colour due to different angles of incidence of light and minor structural differences are intended effects.
6. The products should be protected against mechanical damage both to the face and the underside.
7. Glass products should be installed using ceramic tile adhesives, e.g. C2 type.
8. The adhesive should be evenly spread across the entire surface used for laying tiles. Do not apply the adhesive in spots only. The thickness of the binding layer must be strictly observed.
9. The products should be applied to clean and dry areas.
10. When grouting the tiles, make sure that the adhesive mortar under the cladding has thoroughly dried - wait until all water evaporates from the adhesive used for installation.
11. In order to protect decorative elements against scratches during grouting, cover their face surfaces with e.g. tape.
12. Use fine grain, non-scratch grout for installation of our products. The recommended width of grout is 2 mm.
13. To clean and maintain our products, use gentle detergents that do not cause any damage (scratches) or deterioration of their decorative qualities.
14. Pallets with products should be placed one by one (not stacked), on an even, paved and dewatered ground.

Caution! Any complaints concerning these items will not be considered after the tiles and products have been installed.

For detailed information: www.paradyz.com/instrukcje

27.07.2023